


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 12_V 0.2_A
绝缘电阻 Insulation Resistance	DC500_V.60_Sec.10_MΩMin.
抗电强度 Dielectric Voltage	AC 500_V(50~60HZ) 60_Sec.
操作力 Operating Force	OFF → L: 400±200gf; L → OFF: 200±100gf
	OFF → R: 400±200gf; R → OFF: 200±100gf
负荷寿命 Operation Life With Load	4 DIRECTION: 500±200gf 10,000次

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
9	开关 B SWITCH B	——	1	SX-23D20-G9.2
8	开关 A SWITCH A	——	4	PY-12D01
7	胶垫 WASHER	SILICON RUBBER	1	BLACK
6	PCB 板 PCB BASE	FR-4	1	——
5	端子 TERMINAL	C2680R-EH	7	Sn PLATED
4	胶壳 B HOUSING B	ABS	1	BLACK
3	胶盖 COVER	ABS/PMMA	1	BLACK/WHITE
2	胶柄 KNOB	ABS	1	BLACK
1	胶壳 A HOUSING A	ABS	1	BLACK

A01	绝缘阻抗 → 绝缘电阻 见 ①	王光云	06-07-17
01		赵福希	08-11-04
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM2423			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	COMBINED SWITCH		ITEM NO	CS-41001-A	
UNDER 1	± 0.10	DRAWN	王光云	06-07-17	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	刘瑞富	06-07-21	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-07-21	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.