



示意图 SCHEMATIC

安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 12_V 0.2_A
电压降 Voltage Reduction	0.15 V MAX
绝缘阻抗 Insulation Resistance	DC500V_60Sec. 10_MΩ Min.
抗电强度 Dielectric	AC 500_V(50~60HZ) 60_Sec.

操作力 Operating Force	OFF → L: 400 ± 200gf; L → OFF: 200 ± 100gf
	OFF → R: 400 ± 200gf; R → OFF: 200 ± 100gf
负荷寿命 Operation life with load	4 DIRECTION: 500 ± 200gf 10,000次

9	开关 B SWITCH B		1	TX-23101-R14
8	开关 A SWITCH A		4	PY-12D01
7	垫胶 WASHER	SILICON RUBBER	1	BLACK
6	PCB 板 PCB BASE	FR-4	1	
5	端子 TERMINAL	C2680R-EH	7	Sn PLATED
4	胶身 B HOUSING B	ABS	1	BLACK
3	胶盖 COVER	ABS/PMMA	1	BLACK/WHITE
2	胶柄 KNOB	ABS	1	BLACK
1	胶身 A HOUSING A	ABS	1	BLACK

标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
--------	----------------	----------	---------

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO.	ITEM2319
------	---------	-------------	--------	------------	---------	----------

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	COMBINED SWITCH		ITEM NO	CS-41001-D	
UNDER 1	± 0.10	DRAWN	Sun	11 OCT 03	VERSION	01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED			SCALE		UNIT mm
OVER 10	± 0.50	APPROVED			PROJECTION		

COMAX INDUSTRIAL CO., LTD .