


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 12_V 0.2_A
电压降 Voltage Reduction	0.15 mΩ Max.
绝缘阻抗 Insulation Resistance	DC 500V 10 Sec. 10_MΩ Min.
抗电强度 Dielectric	AC 500_V(50~60HZ) 60_Sec
操作力 Operating Force	OFF—L: 400±200gf; L—OFF: 200±100gf OFF—R: 400±200gf; R—OFF: 200±100gf # DIRECTION: 500±200gf
负荷寿命 Operation Life With Load	10,000次

9	开关 B SWITCH B		1	TX-23I01-R14
8	开关 A SWITCH A		4	PY-12D01
7	垫胶 WASHER	SILICON RUBBER	1	BLACK
6	PCB 板 PCB BASE	FR-4	1	
5	端子 TERMINAL	C2680R-H	7	Sn PLATED
4	胶身 B HOUSING B	ABS	1	BLACK
3	胶盖 COVER	ABS/PMMA	1	BLACK/WHITE
2	胶柄 KNOB	ABS	1	BLACK
1	胶身 A HOUSING A	ABS	1	BLACK
序NO.	零件PART	材料MATERIAL	数量QTY	备注REMARKS

标号REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
-------	----------------	----------	---------

DWG NO. ITEM2404

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	COMBINED SWITCH		ITEM NO	CS-41001-E	
UNDER 1	± 0.10	DRAWN	Zhao f x	18-9-04	VERSION	01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	Kaichi	18-9-04	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	Gao hong	18-9-04	PROJECTION		

**COMAX** INDUSTRIAL CO., LTD .