



安装孔 PIERCING PLAN

示意图 SCHEMATIC

规格 Specifications

| | |
|-------------------------------|--|
| 额定负荷 Ratings | DC 24_V 0.3_A |
| 电压降 Voltage Reduction | 0.15_V Max. |
| 绝缘电阻 Insulation Resistance | DC500_V 60_Sec. 10_MΩ Min. |
| 抗电强度 Dielectric Voltage | AC 500_V (50~60HZ) 60_Sec. |
| 操作力 Operating Force | OFF → L: 400±200gf; L → OFF: 400±200gf OFF → R: 400±200gf; R → OFF: 400±200gf 4 DIRECTION: 500±200gf |
| 负荷寿命 Operation Life With Load | 10,000次 |

| | | | | |
|--------|-----------------|----------------|--------|---------------|
| 13 | 弹簧 SPRING | STEEL | 2 | NATURAL |
| 12 | 胶身 C HOUSING C | ABS | 1 | BLACK |
| 11 | 开关 SWITCHES | | 4 | PY-12D01 |
| 10 | 钢球 STEEL BALL | STEEL | 2 | NATURAL |
| 9 | PCB 板 PCB BASE | FR-4 | 1 | |
| 8 | 垫胶 WASHER | SILICON RUBBER | 1 | BLACK |
| 7 | 滑块 SLIDER | ABS | 1 | BLACK |
| 6 | 端子 B TERMINAL B | C1100 | 2 | NATURAL |
| 5 | 端子 A TERMINAL A | C2680R | 7 | Sn PLATED |
| 4 | 胶身 B HOUSING B | ABS | 1 | BLACK |
| 3 | 胶盖 COVER | ABS | 1 | BLACK |
| 2 | 胶身 A HOUSING A | ABS | 1 | BLACK |
| 1 | 胶柄 KNOB | ABS/SECC | 1 | BLACK/NATURAL |
| 序号 NO. | 零件 PART | 材料 MATERIAL | 数量 QTY | 备注 REMARKS |

| | | | |
|--------|----------------|----------|----------|
| A01 | 修改零件列表见 ① | 曹文斌 | 06-07-17 |
| 01 | 绝缘阻抗变更为绝缘电阻见 ① | 赵福希 | 3 MAR 05 |
| 标号 REV | 内容 DESCRIPTION | 签名 SIGN. | 日期 DATE |

DWG NO. ITEM2467

| | | | | | | | |
|-----------------------------------|--------|----------|-----------------|----------|------------|----------|-------------|
| TOLERANCES UNLESS OTHERWISE SPEC. | | TITLE | COMBINED SWITCH | | ITEM NO | CS-41002 | |
| UNDER 1 | ± 0.10 | DRAWN | 曹文斌 | 06-07-16 | VERSION | A01 | PAGE 1 OF 1 |
| 1 - 10 | ± 0.30 | REVIEWED | 张念明 | 06-07-18 | SCALE | | UNIT mm |
| OVER 10 | ± 0.50 | APPROVED | 林高全 | 06-07-19 | PROJECTION | | |

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.