


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30_V 100m A
初始接触电阻 Initial Contact Resistance	200_mΩ Max.
绝缘电阻 Insulation Resistance	DC250_V 60_Sec. 10_MΩ Min.
抗电强度 Dielectric Voltage	AC 250_V (50~60HZ) 60_Sec.
操作力 Operating Force (gf)	30±20 gf
自由位置 Free Position	5.20mm Max
动作位置 Operating Position	3.20±0.40mm
超行程 Over Travel	2.00±0.40mm
负荷寿命 Operating Life With Load	20,000 Cycles

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO.	ITEM1534
7	端子 TERMINAL	C2680R	3	Ag PLATED		
6	胶壳 HOUSING	PA	1	BLACK C		
5	弹簧 SPRING	SUS	1	NATURAL		
4	接触片 CONTACT CLIP	C5210R	1	Ag CLAD	A02	机械寿命变更为负荷寿命见 ③
3	滑块 SLIDER	PBT	1	BLACK C	A01	3.00 变更为 3.70 见 ⑥
2	胶盖 COVER	PA	1	BLACK C	03	追加自由位置、动作位置、超行程参数 见 ④
1	胶柄 KNOB	POM	1	BLACK C		
				标号 REV	内容 DESCRIPTION	签名 SIGN. 日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	DETECTOR SWITCH		ITEM NO	DS-080	
UNDER 1	± 0.10	DRAWN	曹文斌	2006-06-18	VERSION	A02	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	2006-06-19	SCALE	NO SCALE	UNIT mm
OVER 10	± 0.50	APPROVED	高洪	2006-06-19	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.