


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 12_V 1.0_A
初期接触阻抗 Initial Contact Resistance	30_mΩ Max.
绝缘阻抗 Insulation Resistance	DC500_V 60_Sec 100_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.

操作力	插入力 Insertion force	0.3—3.0_Kgf
Operating Force	拔出力 Extraction force	0.3—3.0_Kgf
负荷寿命	Operating Life With Load	5,000_次 Cycles

6	TIP TERMINAL	C5210	1	Ag PLATED
5	TIP TERMINAL	C5210	1	Ag PLATED
4	RING TERMINAL	C5210	1	Ag PLATED
3	EARTH TERMINAL	C2680	1	Ag PLATED
2	RING	C3602	1	Ni PLATED
1	HOUSING	PBT	1	BLACK C
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ① 修改零件列表 见 ①	王光云	06-06-12
01		赖立辉	1 APR 01
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM1934			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	EAR PHONE JACKS		ITEM NO	EJ-25223	
UNDER 1	± 0.10	DRAWN	王光云	06-06-12	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-12	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-06-13	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.