



规格 Specifications

额定负荷 Ratings	DC 12_V 1.0_A
初期接触电阻 Initial Contact Resistance	30_mΩMax.
绝缘电阻 Insulation Resistance	DC500V_60_Sec.100_MΩMin.
抗电强度 Dielectric Voltage	AC 500_V(50~60HZ)_60_Sec.

操作力	插入力 Insertion force	0.3—3.0_Kgf
Operating Force	拔出力 Extraction force	0.3—3.0_Kgf
负荷寿命	Operating Life With Load	5000_次Cycles

6	BREAK TERMINAL	C2680	1	Ag PLATED
5	EARTH TERMINAL	C2680	1	Ag PLATED
4	NUT ⑥	C3604	1	Ni PLATED
3	RING	C3602	1	Ni PLATED
2	HOUSING	PBT	1	BLACK C
1	TIP TERMINAL	C5210	1	Ag PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A02	增加螺帽见标注 ⑥	张学春	2006-10-26
A01	修改见标注 ①	张学春	06.06.03
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM1975			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	DC POWER JACK		ITEM NO	EJ-3501 W/NUT		
UNDER 1	± 0.10	DRAWN	张学春	2006-10-26	VERSION	A02	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	2006-10-26	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	刘瑞富	2006-10-27	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.