



安装孔 PIERCING PLAN

配套插头 MATE PLUG

规格 Specifications

额定负荷 Ratings	DC 12_V 1.0_A	
初期接触电阻 Initial Contact Resistance	50_mΩ Max.	
绝缘电阻 Insulation Resistance	DC 500_v 60_Sec. 100MΩ Min.	
抗电强度 Dielectric Voltage	AC 500_v(50~60HZ) 60_Sec.	
插拔力 Insertion Extraction Force	插入力(Insertion Force)	0.3 - 3.0 kgf
	拔出力(Extraction Force)	0.3 - 3.0 kgf
负荷寿命 Operating Life With Load	5,000_次 Cycles	

SCHEMATIC		HOUSING COLOR	
YELLOW	EJ-35165-21	TC38-165-21	
YELLOW	EJ-35165-03A	TC38-165-03A	
BLACK	EJ-35165-01	TC38-165-01	

5	TIP SPRING	C5210	1	Ag PLATED
4	RING SPRING (2)	C5210	1	Ag PLATED
3	RING SPRING (1)	C5210	1	Ag PLATED
2	EARTH SPRING	C5210	1	Ag PLATED
1	HOUSING	PBT	1	BLACK
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A03	取消成品型号EJ-35165-02和EJ-35165-03 插拔力从0.4至3.0kgf变更为0.3至3.0kgf见(c) 接触电阻变更为初期接触电阻见(c)	曹文斌	06-07-06
A02	SILVER → Ag PLATED 见标注(b) PHOSPHOR BRONZE → C5210 见标注(b) ADD: EJ-35165-21 见标注(b)	蔡维	06-03-28
A01	更改记录见标注:(a)	蔡维	19-Mar-05
01		孙斌	21-May-02
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	EARPHONE JACKS		ITEM NO	EJ-35165		
UNDER 1	± 0.10	DRAWN	曹文斌	06-07-06	VERSION	A03	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-07-07	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-07-07	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.