



规格 Specifications

额定负荷 Ratings	DC 12_V 20_mA
初期接触阻抗 Initial Contact Resistance	5_Ω Max.
绝缘阻抗 Insulation Resistance	DC 500V 60_Sec. 10_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.
负荷寿命 Operating Life With Load	10,000_次 Cycles

1P - 1T



示意图 SCHEMATIC

4	胶盖 COVER	ABS	1	BLACK C				
3	端子 TERMINAL	C2680R	2	Ag PLATED				
2	弹簧 SPRING	PBSR	1	NATURAL				
1	胶壳 HOUSING	ABS	1	TRANSPARENT	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO. ITEM2374			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SHAKE SWITCH		ITEM NO	HW-061H-CL		
UNDER 1	± 0.10	DRAWN	曹文斌	06-06-26	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-26	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-06-27	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.