

注:P处代表生产日期:YY代表年份=04, 05, 06..., M代表季度=1, 2, 3, ...

### 规格 Specifications

额定负荷 Ratings	5A 125VAC 3A 250VAC
初期接触电阻 Initial Contact Resistance	100 mΩ Max.
绝缘电阻 Insulation Resistance	DC500 V $60 \pm 5$ Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC1000 V(50~60HZ) $60 \pm 5$ Sec.
操作力 Operating Force	70 $\pm$ 25 gf
回复力 Releasing Force	20 gf Min.
动作位置 Operating Position	12.30 $\pm$ 1.20mm
自由位置 Free Position	15.00mm Max.
接触行程 Pre Travel	2.5 mm Max.
过行程 Over Travel	0.3 mm Min.
差程 Movement Differential Travel	1.0 mm Max.
机械寿命 Operating Life Without Load	1,000,000 *cycles
负荷寿命 Operating Life With Load	UL: 6,000 *cycles
	CQC: 50,000 *cycles
	VDE: 50,000 *cycles

11	杠杆	Lever	SUS	1	NATURAL
10	NO 端子	NO Terminal	C2680R	1	Ag PLATED
9	NC 端子	NC Terminal	C2680R	1	Ag PLATED
8	端子触点	Terminal contact	AgNi Alloy	2	NATURAL
7	接触片触点	Contact Point	AgNi Alloy	1	NATURAL
6	接触片	Moving Plate	C5191R	1	Ag PLATED
5	弹簧	Spring	SUS	1	NATURAL
4	COM 端子	Com Terminal	C2680R	1	Ag PLATED
3	胶柄	Knob	PBT	1	BLACK C
2	胶壳	Housing	PBT	1	BLACK C
1	胶盖	Cover	PBT	1	BLACK C
序NO.	零件PART	材料MATERIAL	数量QTY	备注REMARKS	





示意图 SCHEMATIC



安装孔PIERCING PLAN

标号REV	内容DESCRIPTION	签名SIGN.	日期DATE
	DWG NO. ITEM2745		

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE		MICRO SWITCH		ITEM NO		MS-105A01-13(B)	
UNDER 1	± 0.10	DRAWN	徐贤瑜	2006-8-22	VERSION	A01	PAGE	1 OF 1	
1 - 10	± 0.30	REVIEWED	方勇 (代)	2006-8-22	SCALE		UNIT	mm	
OVER 10	± 0.50	APPROVED	刘瑞富	2006-8-22	PROJECTION				

COMAX ELECTRONICS(HUIZHOU) CO., LTD.