

2P - 2T





示意图 SCHEMATIC



安装孔 PIERCING PLAN

① 规格 Specifications

额定负荷 Ratings	DC 25 V 1 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force(gf)	A ← B
	350 ± 150
	(Q) 250 ± 100
负荷寿命 Operating Life With Load	10,000 次 Cycles

8	接触片 CONTACT PLATE	C2680R	2	Ag PLATED
7	锁针 LOCK HOOK	STEEL	1	Ni PLATED
6	弹簧B SPRING B	SUS	2	NATURAL
5	弹簧A SPRING A	STEEL	1	Ni PLATED
4	端子 TERMINAL	C2680R	6	Ag PLATED
3	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
2	胶柄 KNOB	POM	1	NATURAL
1	胶壳 HOUSING	PC	1	BLACK C
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

①

A01	修改零件列表见 ① 增加规格栏见 ①	曹文斌	06-03-31
01		赖立辉	1 FEB 97
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

DWG NO. ITEM1301

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	PUSH BUTTON SWITCH		ITEM NO	PB-22G02-L NS	
UNDER 1	± 0.10	DRAWN	曹文斌	06-03-31	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-04-01	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-04-01	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.