



规格 Specifications

额定负荷 Ratings	DC 30 V 0.1 A
	DC 2 V 2 A (b)
初期接触阻抗 Initial Contact Resistance	80 mΩ Max.
绝缘阻抗 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf) (A → B)	Q (b)
	150 ± 50 gf      250 ± 50 gf
负荷寿命 Operating Life With Load	10,000 Cycles With load

7	端子 TERMINAL	C2680R	6	Ag Plated				
6	锁针 LOCK HOOK	SUS	1	NATURAL				
5	胶壳 HOUSING	PA	1	BLACK C				
4	接触片 CONTACT	C5210R	2	Ag CLAD	A03	修改尺寸和增加规格。见标注 (b)	杨光华	2006-8-28
3	胶盖 COVER	PC	1	GREY	A02		杨光华	06-05-15
2	弹簧 SPRING	SUS	1	NATURAL	A01		杨光华	05-12-21
1	胶柄 KNOB	POM	1	NATURAL	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO. ITEM2591			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	PUSH SWITCH		ITEM NO	PS-221605-L NS		
UNDER 1	± 0.10	DRAWN	杨光华	2006-8-28	VERSION	A03	PAGE 1 OF 1	
1 - 10	± 0.30	REVIEWED	张念明	2006-8-28	SCALE	NO SCALE	UNIT mm	
OVER 10	± 0.50	APPROVED	刘瑞富	2006-8-29	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.