



① 规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC 500_V 60_Sec 100_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force (gf)	A → B	B → A
	250 ± 100	250 ± 100
负荷寿命 Operating Life With Load	10,000 Cycles	

6	弹片	SPRING PLATE	C5210R	1	NATURAL
5	端子	TERMINAL	C2680R	3	Ag PLATED
4	基板	TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片	CONTACT	C5210R	1	Ag CLAD
2	胶柄	KNOB	POM	1	G 2 - 6
1	铁壳	FRAM	SPCC	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	

A01	ADD: 规格 Specifications	见 ①	刘红梅	06-06-12
	修改材料规格栏	见 ①		
01			赖立辉	27 MAY 96
标号 REV	内容 DESCRIPTION		签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH	ITEM NO	SK-12D05-G		
UNDER 1	± 0.10	DRAWN	刘红梅	06-06-12	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-12	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-06-13	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.