



示意图 SCHEMATIC

安装孔 PIERCING PLAN

④ 规格 Specifications

额定负荷 Rdtngs	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘阻抗 Insulation Resistance	DC500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	A → B
	250 ± 100
负荷寿命 Operating Life With Load	10,000 次 Cycles

6	弹片 SPRING	C5210R	1	NATURAL
5	端子 TERMINAL	C2680R	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	1	Ag CLAD
2	胶柄 KNOB	P O M	1	G 2 - 7
1	铁壳 FRAME	S P C C	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ④ C2680R → C2680R 见 ④ C5210R-EH/Ag CLAD → C5210R 见 ④	王光云	06-04-12
02		易金平	18 MAR 02
标号 REV	内容 DESCRIPTION	签名 SIGN	日期 DATE
DWG NO. ITEM0653			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-12D07-G		
UNDER 1	± 0.10	DRAWN	王光云	06-04-12	VERSION	A01	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-04-12	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-04-12	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.