



◎规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force (gf)	(L)	
	A → B	200±100 150±50
负荷寿命 Operating Life With Load	10,000 次 Cycles	

示意图 SCHEMATIC

安装孔 PIERCING PLAN

6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R ◎	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	COPPER WIRE	1	Ag PLATED
2	胶柄 KNOB	P O M	1	G 2 - 9
1	铁壳 FRAME	S P C C	1	Ni PLATED BLACKENED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ◎	王光云	06-05-16
01	C2680R-EH → C2680R 见 ◎	赖立辉	25 JUL 92
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

DWG NO. ITEM0543

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-12F14-G	
UNDER 1	± 0.10	DRAWN	王光云	06-05-16	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-05-16	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-05-16	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.