



① 规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force (gf)	A → B 200 ± 100    B → C 250 ± 100    C → B 200 ± 100    B → A 250 ± 100
负荷寿命 Operating Life With Load	10,000 Cycles

6	弹片 SPRING PLATE	C5210R	1	NATURAL
5	端子 TERMINAL	C2680R	4	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	1	Ag CLAD
2	胶柄 KNOB	P O M	1	G 2 -7
1	铁壳 FRAME	S P T E	1	NATURAL
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications	见 ①	刘红梅	06-06-03
01	修改材料规格栏	见 ①	赖立辉	15 APR 99
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE	

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH	ITEM NO	SK-13D10-G		
UNDER 1	± 0.10	DRAWN	刘红梅	06-06-03	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-05	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-06-06	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.