



◎规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC 500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric	AC 500_V (50~60HZ) 60_Sec.
操作力 Operating Force (gf)	A → B B → C
	C → B B → A
负荷寿命 Operating Life With Load	200±100 300±150
	10,000 次 Cycles

6	弹片 SPRING PLATE	SUS	1	NATURAL
5	端子 TERMINAL	C2680R◎	4	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R◎	1	Ag CLAD
2	胶柄 KNOB	P B T	1	G 5 - 9
1	铁壳 FRAME	S P C C	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ◎	王光云	06-05-04
	C2680R-EH → C2680R 见 ◎		
	C5210R-EH/Ag CLAD → C5210R 见 ◎		
01		赖立辉	20 JAN 01
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
	DWG NO. ITEM1459		

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-13D15-G	
UNDER 1	± 0.10	DRAWN	王光云	06-05-04	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-05-05	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-05-05	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.