



规格 Specifications

额定负荷 Ratings	DC 4 V 0.3 A
初期接触电阻 Initial Contact Resistance	70 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60±5 Sec 100 MΩ
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → A
	C → B	B → C
负荷寿命 Operating Life With Load	125 ± 50	200 ± 50
	10,000 次 Cycles	

示意图 SCHEMATIC

安装孔 PIERCING PLAN

5	端子 TERMINAL	C2680R	4	Ag PLATED			
4	接触片 CONTACT	C5210R	1	Ag CLAD			
3	铁壳 FRAME	SUS	1	NATURAL			
2	胶柄 KNOB	PA	1	BLACK C			
1	胶壳 HOUSING	PA	1	BLACK C			
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	标号 REV	内容 DESCRIPTION	签名 SIGN. 日期 DATE
					DWG NO. ITEM2368		

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-13D21-G 2 RT	
UNDER 1	± 0.10	DRAWN	王光云	06-03-30	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-03-30	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-03-30	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.