

2P - 2T





示意图 SCHEMATIC



安装孔 PIERCING PLAN

① 规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → A
负荷寿命 Operating Life With Load	200 ± 100	
	10,000 Cycles	

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
6	弹片 SPRING PLATE	C5210R	1	NATURAL
5	端子 TERMINAL	C2680R	6	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	2	Ag CLAD
2	胶柄 KNOB	P O M	1	SG 2 - 8
1	铁壳 FRAME	S P C C	1	Sn PLATED

A01	ADD: 规格 Specifications	见 ①	刘红梅	06-06-21
01	修改材料表栏	见 ①	孙斌	24 MAY 01
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE	
DWG NO. ITEM2097				

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH	ITEM NO	SK-22D20-SG		
UNDER 1	± 0.10	DRAWN	刘红梅	VERSION	A01	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	高洪	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.