



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → A
	200 ± 100	350 ± 150
⑤ 负荷寿命 Operating Life With Load	(L)	200 ± 100
		10,000 次 Cycles

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
7⑥	钢珠 STEEL BALL	STEEL	1	NATURAL
6⑥	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R	8	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	2	Ag CLAD
2	胶柄 KNOB	P O M	1	G 3 -15
1	铁壳 FRAME	S P C C	1	Ni PLATED BLACKENED

A02	增加零件材料标示 见⑥	王光云	06-03-23
	机械寿命 → 负荷寿命 见⑤		
A01		王光荣	26 FEB 06
01		赖立辉	23 MAY 92
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM0061			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-23E01-G	
UNDER 1	± 0.10	DRAWN	王光云	06-03-23	VERSION	A02	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-03-23	SCALE	4 : 1	UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-03-30	PROJECTION		

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.