

2P - 4T





示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

① 额定负荷 Ratings	DC 30 V 0.3 A
① 初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	A → B B → C C → D D → C C → B B → A 200 ± 100 gf 250 ± 100 gf 300 ± 150 gf
① 负荷寿命 Operating Life With Load	10,000 Cycles

6	弹片 SPRING PLATE	SUS ①	1	NATURAL
5	端子 TERMINAL	C2680R	12	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	2	Ag CLAD
2	胶柄 KNOB	P O M	1	DG 3 - 9
1	铁壳 FRAME	S P C C	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	接触阻抗更改为初期接触电阻	见 ①	刘红梅	06-06-27
	机械寿命更改为负荷寿命	见 ①		
	增加弹片的材料表栏	见 ①		
01			张渠江	2004/10/18
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE	
DWG NO. ITEM2412				

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-24D18-DG		
UNDER 1	± 0.10	DRAWN	刘红梅	06-06-27	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-27	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-06-27	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.