


示意图 SCHEMATIC



安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B
	200±100
负荷寿命 Operating Life With Load	10,000 次 Cycles

序 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
6	弹片 SPRING PLATE	C5210R	1	NATURAL				
5	端子 TERMINAL	C2680R	3	Ag PLATED				
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW	A01	机械寿命 → 负荷寿命 见 ① 接触阻抗 → 初期接触电阻 见 ①	王光云	06-04-26
3	接触片 CONTACT	C5210R	1	Ag CLAD				
2	胶柄 KNOB	P O M	1	G 2 - 6	01		蔡维	17-11-04
1	铁壳 FRAME	S P T E	1	NATURAL				
					DWG NO. ITEM2430			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-12D11-G		
UNDER 1	± 0.10	DRAWN	王光云	06-04-26	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-04-26	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-04-27	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.