



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	(L)	
	A → B	250±100 150±50
负荷寿命 Operating Life With Load	10,000 次 Cycles	

7	钢珠	STEEL BALL	STEEL	1	NATURAL
6	弹簧	SPRING	STEEL	1	NATURAL
5	端子	TERMINAL	C2680R	3	Ag PLATED
4	基板	TERMINAL BASE	PHENOL RESIN	1	BLACK
3	接触片	CONTACT	C2680R ©	1	Ag PLATED
2	胶柄	KNOB	P O M	1	G 2 - 7
1	铁壳	FRAME	S P C C	1	Ni PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	

A02	PBS → C2680R 见 ©	王光云	06-04-29
A01	接触阻抗 → 初期接触电阻 见 ①	王光云	06-04-09
	机械寿命 → 负荷寿命 见 ①		
02	ADD: 规格 Specifications 见 ①	王光荣	07 APR 04
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-12F04-G	
UNDER 1	± 0.10	DRAWN	王光云	06-04-29	VERSION	A02	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-05-04	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-05-04	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.