



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B
	250 ± 100
负荷寿命 Operating Life With Load	10,000 次 Cycles

6	端子	TERMINAL	C2680R	3	Ag PLATED
5	基板	TERMINAL BASE	PHENOL RESIN	1	BLACK
4	接触片	CONTACT	COPPER WIRE	1	Ag PLATED
3	弹簧	SPRING	STEEL	1	NATURAL
2	胶柄	KNOB	POM	1	G 2 - 15
1	铁壳	FRAME	SPCC	1	Ni PLATED/BLACKENED
序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	

A03	增加尺寸7.5;增加Voltage;见标示①	徐贤瑜	06-06-19
A02	修改零件列表见 ①	曹文斌	06-05-08
	机械寿命变为负荷寿命见 ②		
	绝缘阻抗变更为绝缘电阻见 ①		
A01	接触阻抗变更为初期接触电阻见 ①	何锦洪	25 MAY 05
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM0561			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-12F20-G	
UNDER 1	± 0.10	DRAWN	徐贤瑜	06-06-19	VERSION	A03	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	刘瑞富	06-06-19	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-06-19	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.