



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	(L)
	250 ± 100 150 ± 50
负荷寿命 Operating Life With Load	10,000 次 Cycles

6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	BLACK
3	接触片 CONTACT	COPPER WIRE	1	Ag PLATED
2	胶柄 KNOB	P O M	1	G 2 - 15
1	铁壳 FRAME	S P C C	1	Ni PLATED OR BLACKENED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A03	接触阻抗 —— 初期接触电阻 ③	王光云	06-05-31
A02	机械寿命 —— 负荷寿命 见 ⑥	王光荣	06-03-18
A01	ADD: 规格 Specifications 见 ①	王光荣	06-02-13
01		赖立辉	28 JUL 92
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM0041			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-12F32-G		
UNDER 1	± 0.10	DRAWN	王光云	06-05-31	VERSION	A03	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-02	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	高洪	06-06-03	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.