

1P -2T




示意图 SCHEMATIC

规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	A → B 250 ± 100
负荷寿命 Operating Life With Load	10,000 次 Cycles

6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R ④	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	BLACK
3	接触片 CONTACT	COPPER WIRE	1	Ag PLATED
2	胶柄 KNOB	POM	1	G 2 - 15
1	铁壳 FRAME	SPCC	1	BLACKENED OR Ni PLATED
序 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A03	机械寿命 → 负荷寿命 见 ④	王光云	06-06-15
	接触阻抗 → 初期接触电阻 见 ④		
A02	C2680R-EH → C2680R 见 ④	戴胜春	29-8-05
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH	ITEM NO	SS-12F39-G	
UNDER 1	± 0.10	DRAWN	王光云	VERSION	A03	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.