



示意图 SCHEMATIC

规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC 500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force (gf)	A → B
	250 ± 100
负荷寿命 Operating Life With Load	10,000 次 Cycles

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
7	钢珠 STEEL BALL	STEEL	1	NATURAL
6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	BLACK
3	接触片 CONTACT	C2680R	1	Ag PLATED
2	胶柄 KNOB	P O M	1	G 3.5 - 8 ①
1	铁壳 FRAME	S P C C	1	Ni PLATED

标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
A02	G 3.5 - 8 → G 3.5 - 8 见 ①	王光云	06-05-10
A01	ADD: 规格 Specifications 见 ①	王光云	06-04-29
01		赖立辉	16 JAN 01

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH	ITEM NO	SS-12F60-G	
UNDER 1	± 0.10	DRAWN	王光云	06-05-10	VERSION	A02
1 - 10	± 0.30	REVIEWED	张念明	06-05-10	SCALE	PAGE 1 OF 1
OVER 10	± 0.50	APPROVED	林高全	06-05-10	PROJECTION	UNIT mm

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.