



示意图 SCHEMATIC

① 安装孔 PIERCING PLAN

② 规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force(gf)	A ⇌ B 250±100
机械寿命 Operating Life Without Load	10,000 Cycles

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
7	钢珠 STEEL BALL	STEEL	2	NATURAL
6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	1	Ag CLAD
2	胶柄 KNOB	P O M	1	G 2 - 10
1	铁壳 FRAME	S P C C	1	Sn PLATED

A01	ADD: 规格 Specifications 表栏 见 ① 修改材料表栏 见 ①	刘红梅	06-07-19
01		赖立辉	13 FEB 01
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

DWG NO. ITEM1906

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-12H15-G	
UNDER 1	± 0.10	DRAWN	刘红梅	06-07-19	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-07-20	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-07-21	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.