



规格 Specifications

| | |
|-----------------------------------|------------------------------|
| ① 额定负荷 Ratings | DC 30_V 0.3_A |
| 初期接触电阻 Initial Contact Resistance | 30_mΩ Max. |
| 绝缘电阻 Insulation Resistance | DC 500_V 60_Sec. 100_MΩ Min. |
| 抗电强度 Dielectric Voltage | AC 500_V (50~60HZ) 60_Sec. |

| | |
|---------------------------------|-----------------|
| 操作力 Operating Force (gf) | A ↔ B |
| | 200±100 |
| ① 负荷寿命 Operating Life With Load | 10,000 次 Cycles |

| 6 | 弹片 SPRING PLATE | SUS | 1 | NATURAL |
|------|------------------|--------------|--------|------------|
| 5 | 端子 TERMINAL | C2680R | 6 | Ag PLATED |
| 4 | 基板 TERMINAL BASE | PHENOL RESIN | 1 | YELLOW |
| 3 | 接触片 CONTACT | C5210R | 2 | Ag PLATED |
| 2 | 胶柄 KNOB | P O M | 1 | G 2 - 9 |
| 1 | 铁壳 FRAME | S P C C | 1 | Sn PLATED |
| 序NO. | 零件 PART | 材料 MATERIAL | 数量 QTY | 备注 REMARKS |

| A01 | 机械寿命 → 负荷寿命 见 ① | 王光云 | 06-06-10 |
|------------------|-------------------|----------|-----------|
| | 接触阻抗 → 初期接触电阻 见 ① | | |
| 01 | | 易金平 | 18 NOV 03 |
| 标号 REV | 内容 DESCRIPTION | 签名 SIGN. | 日期 DATE |
| DWG NO. ITEM2308 | | | |

| | | | | | | | |
|-----------------------------------|--------|----------|--------------|----------|------------|------------|-------------|
| TOLERANCES UNLESS OTHERWISE SPEC. | | TITLE | SLIDE SWITCH | | ITEM NO | SS-22F47-G | |
| UNDER 1 | ± 0.10 | DRAWN | 王光云 | 06-06-10 | VERSION | A01 | PAGE 1 OF 1 |
| 1 - 10 | ± 0.30 | REVIEWED | 张念明 | 06-06-10 | SCALE | | UNIT mm |
| OVER 10 | ± 0.50 | APPROVED | 高洪 | 06-06-13 | PROJECTION | | |

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.