



规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric	AC 500_V (50~60HZ) 60_Sec.

操作力 Operating Force (gf)	A ← B	B ← A
	C ← B	B ← C
负荷寿命 Operating Life With Load	150 ± 50	200 ± 100

6	弹片 SPRING	C5210R	1	NATURAL
5	端子 TERMINAL	C2680R①	8	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R①	2	Ag CLAD
2	胶柄 KNOB	P O M	1	G 2 - 7
1	铁壳 FRAME	S P C C	1	Sn PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ①	王光云	06-03-30
	C2680R-EH → C2680R 见 ①		
	C5210R-EH/Ag CLAD → C5210R 见 ①		
01		赖立辉	9 DEC 97
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM0649			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-23D08-G		
UNDER 1	± 0.10	DRAWN	王光云	06-03-30	VERSION	A01	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-03-31	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-03-31	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.