



①规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A — B	B — A
	200±100	350±150
负荷寿命 Operating Life With Load	10,000 次 Cycles	

7	钢珠 STEEL BALL	STEEL	2	NATURAL
6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R ①	8	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R ①	2	Ag CLAD
2	胶柄 KNOB	P O M	1	G 4 - 15
1	铁壳 FRAME	S P C C	1	Ni PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	ADD: 规格 Specifications 见 ①	王光云	06-04-24
	C2680R-EH —— C2680R 见 ①		
	C5210R-EH/Ag CLAD —— C5210R 见 ①		
01		赖立辉	2 JUN 92
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM0172			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH	ITEM NO	SS-23E03-G		
UNDER 1	± 0.10	DRAWN	王光云	VERSION	A01	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	PROJECTION			

**COMAX** ELECTRONICS (HUIZHOU) CO.,LTD.