



示意图 SCHEMATIC

安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → C
	C → B	B → A
负荷寿命 Operating Life With Load	200 ± 100	250 ± 100

7	端子 TERMINAL	C2680R	8	Ag PLATED
6	接触片 CONTACT	C5210R	2	Ag CLAD
5	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
4	弹簧 SPRING	SUS	1	NATURAL
3	钢珠 STEEL BALL	SUS	2	NATURAL
2	胶柄 KNOB	POM	1	G 2 - 9
1	铁壳 FRAME	SPCC	1	Ni PLATED
序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	修改零件列表见 (a)	曹文斌	06-04-17
01	增加规格栏见 (a)		
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-23E10-G		
UNDER 1	± 0.10	DRAWN	曹文斌	06-04-17	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-04-17	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-04-18	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.