



① 规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → C
	C → B	B → A
机械寿命 Operating Life Without Load	250 ± 100	350 ± 150
	10,000 次 Cycles	

序NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
7	钢珠 STEEL BALL	STEEL	2	NATURAL
6	弹簧 SPRING	STEEL	3	NATURAL
5	端子 TERMINAL	C2680R	8	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	BLACK
3	接触片 CONTACT	C2680R	2	Ag PLATED
2	胶柄 KNOB	P O M	1	BLACK C
1	铁壳 FRAME	S P C C	1	Ni PLATED

A01	ADD: 规格 Specifications 见①	刘红梅	06-07-10
	更改材料表栏 见①		
01		赖立辉	8 MAY 01
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM1921			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-23F22-AC 5	
UNDER 1	± 0.10	DRAWN	刘红梅	06-07-10	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-07-10	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-07-12	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.