



规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
① 初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.
操作力 Operating Force (gf)	A → B B → C C → D
	D → C C → B B → A
① 负荷寿命 Operating Life With Load	10,000 次 Cycles

7	钢珠 STEEL BALL	STEEL	2	NATURAL
6	弹簧 SPRING	SUS	1	NATURAL
5	端子 TERMINAL	C2680R	10	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	2	Ag CLAD
2	胶柄 KNOB	P O M	1	A 3 - 12
1	铁壳 FRAME	S P C C	1	Ni PLATED
序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A01	机械寿命 —— 负荷寿命 见 ①	王光云	06-05-24
A01	接触阻抗 —— 初期接触电阻 见 ①		
02		何景洪	28-12-04
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH	ITEM NO	SS-24E01-A		
UNDER 1	± 0.10	DRAWN	王光云	06-05-24	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-05-24	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	林高全	06-05-24	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.