



规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
① 初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_M Min.
抗电强度 Dielectric	AC 500_V (50~60HZ) Sec.
操作力 Operating Force (gf)	A → B B → C C → D D → C C → B B → A
	200±100 250±100 250±100
(H)	80±20 100±50 100±50
负荷寿命 Operating Life With Load	10,000 次 Cycles

6	弹片 SPRING PLATE	SUS	1	NATURAL
5	端子 TERMINAL	C2680R	24	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	C5210R	4	Ag CLAD
2	胶柄 KNOB	P O M	1	G 2 - 9
1	铁壳 FRAME	S P C C	1	Sn PLATED
序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS

A02	接触阻抗 → 初期接触电阻 见 ①	王光云	06-05-04
A01	ADD: 规格 Specifications 见 ②	王光云	06-03-09
01		赖立辉	11 DEC 96
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
DWG NO. ITEM1169			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH	ITEM NO	SS-44F28-G		
UNDER 1	± 0.10	DRAWN	王光云	VERSION	A02	PAGE	1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.